

SPECIFICATIONS FOR DIGITAL THERMOHYGTOMETER

NO	SPECIFICATIONS	SPECIFY or Y/N
1	Sumultaneously monitors both indoor room temperature and indoor room humidity on a large difital screen with dual display of temperature and humidity readings which can be easily read from acroee a room	
2	Approximate product size: Preferably 7-10cm (width) x 9-12cm (height)	
3	Range of readings: Temperature readings to range from approximately 0-50 degrees celsius (°C), and humidity reading to range from approximately 20-99%	
4	Resolution of readings: Temperature readings in 0.1 degrees celsius (°C) increments and humodity reading in 1% increments	
5	Minimum/maximum memory feature - able to recall and display minimum/maximum indoor roo temperature and minimum/maximum indoor room humodity over anytime period. Reset function should be available	
6	Able to stand upright on its own for tabletop use or be mounted to wall	
7	Battery operated (preferably operated with 1 x AAA battery). Delivery of stock must include supply of at east 24 (twenty-four) units of complatible batteries with a minimum shelf life of 3 years or longer	
8	At least one-year limited warranty from manufacturer/ supplier	
9	Each thermometer must be calibrated against European or Americal standard AND provided with individually serial-numbered calibration certificate. The inclusion of a calibration certificate must stated in the brochure/pamphlet	
10	Supplier is to submit product brochure/pamphlet information together with quotation	
11	BRAND:	
12	UNIT PRICE:	
13	TOTAL PRICE:	
14	QUANTITY: 28 units	
15	WARRANTY:	
16	DELIVERY:	